



---

## ENLOGIC EDGE SERIES

## FIRMWARE RELEASE NOTES

---

Version 1.1.0

01-12-2022

## TABLE OF CONTENTS

|   |          |
|---|----------|
| <b>1 GENERAL.....</b>                   | <b>3</b> |
| 1.1    Scope .....                      | 3        |
| 1.2    Abbreviations and acronyms ..... | 3        |
| <b>RELEASED FILES.....</b>              | <b>4</b> |
| 1.3    Packaged File.....               | 4        |
| 1.4    Software Version.....            | 4        |
| <b>2 PRODUCT FAMILY.....</b>            | <b>4</b> |
| <b>3 SKU SUPPORTED .....</b>            | <b>4</b> |
| <b>4 PDU FEATURES ENABLED.....</b>      | <b>5</b> |

## 1 GENERAL

### 1.1 SCOPE

This document is the Release Notes for Enlogic Edge Series Firmware Version 1.1.0

### 1.2 ABBREVIATIONS AND ACRONYMS

A list of the principal abbreviations and acronyms used in the document is provided here for a better understanding of this document.

|             |                                       |
|-------------|---------------------------------------|
| <b>PDU</b>  | Power Distribution Unit               |
| <b>GUI</b>  | Graphical User Interface              |
| <b>SSH</b>  | Secure shell                          |
| <b>SNMP</b> | Simple Network Management Protocol    |
| <b>SMTP</b> | Simple Mail Transfer Protocol         |
| <b>LDAP</b> | Lightweight Directory Access Protocol |
| <b>CLI</b>  | Command Line Interface                |
| <b>Conf</b> | Configuration                         |
| <b>CB</b>   | Circuit Breaker                       |
| <b>FTPS</b> | File Transfer Protocol Secure         |
| <b>MAC</b>  | Media Access Control                  |
| <b>NTP</b>  | Network Time Protocol                 |
| <b>IP</b>   | Internet Protocol                     |
| <b>ETH</b>  | Ethernet                              |
| <b>SKU</b>  | Stock Keeping Unit                    |

## RELEASED FILES

### 1.3 PACKAGED FILE

Enlogic.FW

| Image File | MD5                              |
|------------|----------------------------------|
| Enlogic.FW | c3a390ac531f5a076522db164ba7e8b8 |

### 1.4 SOFTWARE VERSION

FIRMWARE VERSION – 1.1.0

WEBUI – 1.28

BOOT VERSION – 1.3

## 2 PRODUCT FAMILY

| Product Type                                  | Description  |
|---|--|
| <b>Input Metered (MI)</b>                     | PDU that have ability for aggregate power monitoring   |
| <b>Metered and Switched per Outlet (MOSO)</b> | PDU that have ability to aggregate outlet level power monitoring and outlet level switching capability |

## 3 SKU SUPPORTED

| Type  | SKU Numbers  |
|---|--|
| <b>Input Metered (MI)</b>                     | <a href="#">ES1337</a> , <a href="#">ES1811</a> , <a href="#">ES1325</a> , <a href="#">ES1326</a> , <a href="#">ES1311</a> |
| <b>Input Metered, Outlet Switched (MS)</b>    | ES2306   |
| <b>Metered and Switched per Outlet (MOSO)</b> | <a href="#">ES6329</a> , <a href="#">ES6325</a> , <a href="#">ES6810</a>   |

## 4 PDU FEATURES ENABLED

| Features  | Input Metered (MI) | Metered and Switched per Outlet (MOSO) |
|---|--------------------|--|
| <b>Design</b> <ul style="list-style-type: none"> <li>• Low profile, space saving design</li> <li>• Ultra-low-profile circuit breakers on most models</li> <li>• Adjustable tool-less mounting system</li> </ul>   | YES                | YES                                    |
| <b>PDU Power Monitoring</b> <ul style="list-style-type: none"> <li>• PDU level watt hour power metering (kWh)</li> <li>• PDU level power measurements (W)</li> <li>• Input phase level power measurements (V, A, VA, kWh, pf)</li> <li>• Circuit Breaker level current measurements</li> <li>• High accuracy, billing grade metering capabilities</li> <li>• Embedded memory log to record/view/report historical data</li> <li>• User customizable alarm thresholds &amp; notifications</li> </ul> | YES                | YES                                    |
| <b>Outlet level switching</b> <ul style="list-style-type: none"> <li>• Remote ON/OFF Power control by individual outlet</li> <li>• User defined power-on time delay to sequence IT equipment</li> <li>• Automatic sequencing to avoid inrush current overload</li> <li>• Controlled with assignable roles and user access</li> </ul>  | NA                 | YES                                    |
| <b>Outlet level power monitoring</b> <ul style="list-style-type: none"> <li>• Outlet level watt-hour power metering(kWh)</li> <li>• Outlet level power measurements (V, A, VA, W, pf)</li> </ul>  | NA                 | YES                                    |
| <b>Environmental management</b> <ul style="list-style-type: none"> <li>• Optional Plug and Play environmental sensors including temperature, humidity and water leak</li> </ul>   | YES                | YES                                    |
| <b>Physical security Management</b> <ul style="list-style-type: none"> <li>• Rack access monitoring with door contact switch</li> <li>• User customizable alarm thresholds and notifications</li> </ul>   | YES                | YES                                    |
| <b>Network management and local display interface</b> <ul style="list-style-type: none"> <li>• Active LED display for power measurements</li> <li>• OLED Display with high contrast ratio, easy to navigate menu and visual graphic bars for phase load balancing</li> </ul>  | YES                | YES                                    |

|  |     |     |
|--|-----|-----|
| <ul style="list-style-type: none"><li>• Full featured network management and alerting capabilities supporting HTTP, HTTPS, SSH, SNMP, FTP and EMAIL</li><li>• Strong encryption, passwords and advanced authorization options including local permissions, LDAP and Active Directory</li><li>• Daisy Chain up to 4 Rack PDU and 16 environmental sensors through single IP address</li></ul> |     |     |
| <b>Branch circuit Load Monitoring</b>  | YES | YES |
| <b>CIRCUIT breaker status</b>  | NA  | YES |